

Virtuose 6D TAO™

The Virtuose 6D TAO is a 6 active degrees-of-freedom haptic device with a passive gripper.

Thanks to its large workspace, interaction capacities and EtherCAT interface, it enables and eases a slave robot control.

Nuclear Teleoperation # Industrial Teleoperation

6 ACTIVE DEGREES-OF-FREEDOM – PASSIVE GRIPPER

- ✓ Passive weight balancing
- ✓ EtherCAT/Ethernet communication system
- 🗸 TREH Handle (TeleRobotic Ergonomic Handle), designed for Master Slave operations, including a dead-man function
- ✓ Button Box: 4 dedicated buttons with switch to freeze the pinch
- ✓ Reduced weight, allowing transportation without specific equipment
- ✓ Dedicated plug-ins for: Unity3D[™], 3DExperience[™], Catia[™] & Delmia[™] V5, Solidworks[™], Siemens Tecnomatix[™] & Classic Jack[™]
- ✓ Drivers (binary and/or source code) available for: Python™, Worldviz Vizard™, ROS™, CHAI3D™, ODE™, Matlab Simulink™, Nvidia Flex™, ...



MODULARITY

The user takes hold of the haptic device using a gripper or handle placed at the tip (called "end-effector").

The gripping tool is equipped with two buttons, one 3 positionbutton and a 7th DOF with a passive gripper. The button box is equipped with three buttons and three multiple-position buttons.





TECHNICAL

Translation workspace	1330 x 575 x 1020 mm
Rotation Workspace	330° x 130° x 270°
Translation force: Peak, Continuous	34 N , 9.5 N
Rotation force: Peak, Continuous	5 Nm , 1.4 Nm
Position resolution	0.013 mm
Rotation resolution	0.0018°
Device Weight	12 kg
ELECTRICAL	
Power supply	100-240 VAC 50/60Hz single phase
Consumption	Average consumption 200W
	Max consumption: 540W
Software	
Maximum translation stiffness	2000 N/m
Maximum rotation stiffness	40 Nm/rad
Update Rate	1000 Hz

The Virtuose 6D, Virtuose 6D TAO and Virtuose 3D are also available upside-down. We are available to discuss with you any specific request for integration.

HAPTION S.A.

Atelier relais ZA Route de Laval – 53210 SOULGE SUR OUETTE – France Tel. 18062020228 E mail: 18062020228@qq.com https://www.jingtianrobots.com